

Light Compaction Equipment

LG and LH - Forward and Reversible Compaction Plates

- Low vibration handle for operator safety and comfort
- Suitable for block paving
- Specially designed to compact soil in confined areas such as trenches and parking lots
- Different widths of bottom plates
- Diesel or petrol models available



Model	LG160	LG160	LG160	LG160	LG200	LG200	LG200
Operating weight (kg)	155	161	169	175	217	231	247
Base plate dimensions (mmxmm)	330x655	450x655	330x655	450x655	500x700	500x700	500x700
Engine power (kW)	4.1	4.1	2.8	2.8	4.8	3.1	3.1
Centrifugal force (kN)	28.0	28.0	28.0	28.0	36.0	36.0	36.0
Fuel Type	Petrol	Petrol	Diesel	Diesel	Petrol	Diesel	Diesel
Starting Mechanism	-	-	-	-	-	Manual	Electric

Model	LG300	LG300	LG300	LG300	LG300	LG300	LG400	LG400
Operating weight (kg)	265	270	282	302	287	307	398	436
Base plate dimensions (mmxmm)	500x768	600x768	500x768	500x768	600x768	600x768	650x967	650x967
Engine power (kW)	5.8	5.8	4.2	4.2	4.2	4.2	7.7	6.2
Centrifugal force (kN)	40.0	40.0	40.0	40.0	40.0	40.0	52.0	52.0
Fuel Type	Petrol	Petrol	Diesel	Diesel	Diesel	Diesel	Petrol	Diesel
Starting Mechanism	-	-	Manual	Electric	Manual	Electric	-	Electric

Model	LG500	LG500	LG500	LG500	LH700	LH800
Operating weight (kg)	490	505	510	525	780	820
Base plate dimensions (mmxmm)	550x900	750x900	550x900	750x900	660x1050	660x1050
Engine power (kW)	8.2	8.2	8.2	8.2	11.0	11.0
Centrifugal force (kN)	60.0	60.0	60.0	60.0	95.0	95.0
Fuel Type	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
Starting Mechanism	Manual	Manual	Electric	Electric	Electric	Radio Remote Controlled

LP - double drum rollers

- Effortless manouvrability with fully hydraulic steering and transmission systems
- Low hand and arm vibration handle on LP6500
- Hydraulic oil-cooling system for long working times
- Open design for easy maintenance and service
- Interchangeable drum modules 630mm or 850mm width on LP8504
- Bluetooth remote control on LP8504

Model	LP6500	LP6500	LP750	LP750	LP8504	LP8504
Type	double drum roller		double drum roller		trench compactor	
Operating weight (kg)	696	716	993	1009	1573	1675
Smooth/Padfoot	S	S	S	S	P	P
Drum width (mm)	650	650	750	750	630	850
Centrifugal force (kN)	21	21	25	25	65	65
Net power (kW)	6.8	6.8	8.9	8.9	12.5	12.5
Starting mechanism	Manual	Electric	Manual	Electric	Bluetooth remote controlled	



Atlas Copco Construction Equipment Australia

Freecall (24 x 7 x 365): 1300 155 337

www.atlascopco.com.au

Sustainable Productivity

